

Miniature Contacts (9.5 mm)

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Closed loop
- ▶ Ideal for window frames, thin door frames, or security screens
- ▶ Versatile

The recessed magnetic contacts have lead connections. They have a true miniature design and are shorter than compact design contacts. They can be used on window frames, thin door frames, or security screens.

The contacts are available in brown or white.

Region	Regulatory compliance/quality marks	
Europe	CE	
USA	UL	cULus: AMQV: Connectors and Switches (UL634), AMQV7: Connectors and Switches Certified for Canada (ULC/ORD-C634)

Installation/configuration notes

Compatibility information

The magnetic contacts are compatible with control panels that accept contact inputs.

Technical specifications

Electrical

Maximum operating voltage in VDC	30
Maximum conductive current in A	0.5
Maximum contact rating in W	10

Maximum initial contact resistance in mΩ	100
Switch configuration type	Single pole single throw (SPST)
Maximum switching voltage in VAC/VDC	24/24
Maximum switching current in A	0.1

Mechanical

Gap width in mm	12.7
Gap width in inch	0.5
Dimension in cm (Ø x D) (contact)	0.95 x 1.55
Dimension in inch (Ø x D) (contact)	0.37 x 0.61
Dimension in cm (Ø x D) (magnet)	0.95 x 1.55
Dimension in inch (Ø x D) (magnet)	0.37 x 0.61
Cable type	22 AWG leads standard
Cable length in cm	30.5
Cable length in inch	12

Environmental

Minimum operating temperature in °C	-40
Maximum operating temperature in °C	60
Minimum operating temperature in °F	-40
Maximum operating temperature in °F	140

Ordering information

ISN-CMINI-10B CNTCT 3/8" MINIRECS- 10PK BRN

Brown recessed contact with lead connections. 0.95 cm (0.37 in.) diameter, 1.25 cm (0.5 in) gap width. **Package contains ten contacts and ten magnets.**

Order number **ISN-CMINI-10B**

ISN-CMINI-10W Miniature contact, 3/8", white, 10pcs

White recessed contact with lead connections. 0.95 cm (0.37 in.) diameter, 1.25 cm (0.5 in) gap width. **Package contains ten contacts and ten magnets.**

Order number **ISN-CMINI-10W**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Tel.: +49 (0)89 6290 0
Fax: +49 (0)89 6290 1020
de.securitysystems@bosch.com
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com