BOSCH

ISC-PB1-100 Panic button, GLT

- ▶ Wired panic hold-up button
- ▶ For connecting to an intrusion panel
- ▶ Tamper contact
- ▶ Surface– or flush–mounting of the cable
- ▶ Compatible with optional cap with cover

The panic button is used for unobtrusively and manually triggering alarms at work places that are in potential danger of being held up, such as banks, jewelry shops, businesses, private households etc.

System overview

This button mounts easily in discreet locations with its tool-less disassembly feature. When activated sends a panic alarm signal to the monitoring system.

Functions

If optional seal is used and the button is pressed this seal will tear giving an indication of which button is pressed if more than one is connected in a loop.

Regulatory information

Region	Regulatory compliance/quality marks	
Europe	CE	[ISC-PB1-100, AD100GLT, ND 100 GLT]
	EN50131	TAP-66/2015 [ND100 GLT]
Germany	VdS	G 195065, C ND 100 GLT G 195065

Installation/configuration notes

This device can be surface installed using the supplied adhesive or drill holes.

Parts included

Quantity	Component
1	Panic button

Quantity	Component
1	Adhesive seal
1	Installation note

Technical specifications

Mechanical

Dimensions (Ø x H) (cm)	8.10 cm x 3.10 cm
Dimensions (Ø x H) (in)	3.18 in x 1.22 in
Color	Gray
Color (RAL)	RAL 9002 Gray white
Material	Plastic
Weight (g)	70 g

Environmental

Operating temperature (℃)	0 ℃ – 50 ℃
Operating temperature (℉)	32 ℉ – 122 ℉
Operating relative humidity, non-condensing (%)	0% – 95%
IP rating	IP40
Environmental class (VdS 2110)	II

Electrical

Operating voltage (VDC)	12 VDC – 30 VDC

Ordering information

ISC-PB1-100 Panic button, GLT
Conventional panic button for unobtrusively and
manually triggering alarms
Order number **ISC-PB1-100 | 4.998.117.557**

Accessories

3902115343 Sealing cap with cover
For additional protective cover to prevent false alarms
Order number **3902115343 | 3.902.115.343**

IMI-SEAL-P Paper seal for hold-up buttons (10 pcs)
Seal paper for hold-up buttons, 10pcs
Order number **IMI-SEAL-P | F.01U.275.632**